

POE SWITCH(UN MANAGED)
POE SWITCH(WEB MANAGEMENT)
BRACKETS
NETWORK CABLES
KEYBOARD
TESTER
ADAPTER



HIKVISION گروه حفاظتی **ایمن**
نماینده رسمی دوربین و تجهیزات حفاظتی **هایک** ویزن در استان اصفهان

اصفهان، خیابان طالقانی، نبش بن بست ۱۷ ۰۳۱۳۲۳۶۴۴۲۴ – ۰۳۱۳۲۳۳۸۷۵۲
مشتری مداری، قیمت مناسب، کیفیت و خدمات پایدار

SWITCH

	Model	Appearance	Description	price
POE Switch(Un managed)	DS-3E0105P-E		L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	3,020,000
	DS-3E0109P-E		L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	8,120,000
	DS-3E0318P-E		L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	17,400,000
	DS-3E0326P-E		L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	29,360,000
	DS-3E0109P-E/M		1. L2, Unmanaged, 8 100M PoE port, 1 100M uplink port; 2. 802.3af/at self- adaptive, PoE power budget 58W; 3. Long distance transmission: max. 250m per port in "Extend" mode; 4. VIP port: Port1-2, QoS priority; 5. Lightning Protection: 6KV per port; 6. Metal casing;	COOMING SOON
	DS-3E0318P-E/M		1. L2, Unmanaged, 16 100M PoE port, 1 1000M RJ45 uplink port, 1 1000M independent SFP uplink port; 2. 802.3af/at self- adaptive, PoE power budget 135W; 3. Four Working Mode: a. "Extend" Mode: Port 9-16, max. 250m long distance transmission; b. "Isolate" Mode: each 100M port as a single Vlan to isolate the port communicaiton and prevent network storm; c. "Standard" Mode: default, normal working mode; d. "Priority" Mode: VIP port, port1-8, QoS priority; 5. Lightning Protection: 6KV per port; 6. Metal casing;	COOMING SOON
	DS-3E0326P-E/M		1. L2, Unmanaged, 24 100M PoE port, 1 1000M RJ45 uplink port, 1 1000M independent SFP uplink port; 2. 802.3af/at self- adaptive, PoE power budget 225W; 3. Four Working Mode: a. "Extend" Mode: Port 17-24, max. 250m long distance transmission; b. "Isolate" Mode: each 100M port as a single Vlan to isolate the port communicaiton and prevent network storm; c. "Standard" Mode: default, normal working mode; d. "Priority" Mode: VIP port, port1-8, QoS priority; 5. Lightning Protection: 6KV per port; 6. Metal casing;	COOMING SOON

POE Switch(Web management)	DS-3E1310P-E		L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	9,280,000
	DS-3E1318P-E		L2, Web managed, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	20,880,000

CABLES

Network cables	DS-1LN5E-S		UTP / CAT.5e / Indoor PVC / 24AWG Full 305m OFC / 0.50mm CM Rating Default Color: Grey	5,840,000
	DS-1LN6-UU		UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	6,780,000

BRACKETS

DS-1602ZJ-pole		Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for: DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	1,720,000
----------------	---	--	-----------

DS-1662ZJ		Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	1,430,000
DS-1663ZJ		Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	580,000
DS-1693ZJ		Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner	9,280,000
DS-1681ZJ		Ceiling mount , Hik white , Aluminum alloy Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	560,000
DS-1602ZJ		Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	1,150,000
DS-1273ZJ-135B		Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx	2,430,000

KEYBOARD

	DS-1100KI		Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	58,340,000
	DS-1005KI		network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	15,380,000

TESTER

IP Tester	IPC-4300H		IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	14,000,000
CCTV Tester	DS-TT-X41T		7" LCD Screen, Support HDTVI camera, Up the Coax, 12 VDC output	14,570,000

ACCESS CONTROL

DS-K2800 Series Access Controller	DS-K2804		Four-door Access Controller , Accessible Card Reader: 4 Wiegand readers; Input interface: Door Magnetic×4, Door Switch×4, Case Input×4; Output interface: Door Switch Relay×4, Alarm Relay×4; Uplink Communication Interface: TCP/IP Network Interface; Storage with 10,000 cards information and 50,000 access control events	9,700,000
	DS-K1101MK		Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 120 Gang Box Only	2,230,000

DS-K1100 Series Card Reader	DS-K1102M		Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 &120 Gang Box	2,230,000
	DS-K1102MK		Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 & 120 Gang Box	3,420,000
	DS-K1104M		Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, Vandal Proof, IP 65, Applied for 86 & 120 Gang Box	4,290,000
	DS-K1801M		Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	1,750,000
	DS-K1801MK		Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	1,910,000
Card Sender	DS-K1F100-D8E		Plug-and-play USB with no-driver technology, Supports various card types (Mifare card, and EM card)	11,130,000
Pro Magnetic Lock	DS-K4T100		Electric Bolt, Polished and Brushed Stainless Steel, Support Thrust of 800kg; Working Current: 900mA(Startup Current), 100mA (Standby), DC12V	3,420,000
	DS-K4H250S		Single-door Magnetic Lock, supports static linear thrust of 250kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	4,290,000
	DS-K4H250D		Double-door Magnetic Lock, supports static linear thrust of 2 x 250kg, Working Current: 12V/500mA×2 24V/250mA×2	8,740,000

Eco Magnetic Lock	DS-K4H188S		Single-door Magnetic Lock, supports static linear thrust of 188kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	1,910,000
Pro Bracket for Magnetic Lock	DS-K4T100-U2		Upper and lower U-bracket of Electric Bolt, for Using with DS-K4T100	3,420,000
	DS-K4H250-LZ		LZ-Bracket of Magnetic Lock, for DS-K4H250S/D	1,910,000
	DS-K4H250-U		U-Bracket of Magnetic Lock, for DS-K4H250S/D	960,000
Eco Bracket for Magnetic Lock	DS-K4H188-LZ		LZ-Bracket of Magnetic Lock, for DS-K4H188S/D	1,360,000
Door release button	DS-K7P01		aluminum alloy panel, metal button, Dimension(L×W×H): 86×86×20mm(3.39×3.39×0.79")	730,000
DS-K1T8 Series Standalone Access Control Terminal	DS-K1T803MF		LCD Display Standalone Access Control Terminal , Support Access Control and Time Attendance Function, Optical Fingerprint Module, 3,000 Fingerprints Capacity, Support Wi-Fi & TCP-IP, Stand-alone Operation, Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc	8,740,000

DS-K1T200 Series IP-based Fingerprint Access Control Terminal	DS-K1T200MF-C		2.8 inch LCD-TFT Screen IP-based Fingerprint Access Control Terminal , Built-in Mifare card reading module and 2 Megapixels camera , Max. 9500 fingerprints, Max. 100,000 cards No.and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	19,870,000
DS-K1T105 Series Standalone Access Control Terminal	DS-K1T105M-C		2.8 inch LCD-TFT Screen Standalone Access Control Terminal , Built-in Mifare card (EM card) reading module, 2 Megapixels camera , Max. 100,000 cards No., and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	10,340,000
	DS-K1T801M		Standalone Access Control Terminal , Built-in Mifare card reading module, Max. 3,000 cards No., TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	2,710,000
	DS-K1T802M		LCD Display Screen Standalone Access Control Terminal , Built-in Mifare card reading module, Max. 3,000 cards No., and Max. 10,000 access control events records, TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	4,620,000
Card	S50+TK4100		EM + Mifare	90,000
ADAPTER				
	Power Adapter		12V/1A	130,000